

TEMPERATURE METER

CKT-800 SERIES HANDHELD MULTI-CHANNEL TEMPERATURE METER

04



■ INTERFACE:

·USB

BRIEF INTRODUCTION

CKT-800 series handheld multi-channel temperature meter adopts high-performance ARM micro processor, can collect multi-channel temperature data simultaneously and response quickly. CKT-800 series has the function of broken thermocouple checking, high/low beep function and communication transmission. Ultra-low power consumption and high density SMD assembly technology. True-color TFT liquid crystal display, keypad and touch screen double control. It is Li-battery powered. USB communication. Switch in both English and Chinese. The standard computer software can realize the data analysis.

STANDARD ACCESSORIES



K type thermocouple wire
1pcs/channel (2 meters/pcs)



DC power adaptor



Lithium battery



Mini-USB communication cable

■ FEATURES:

- Error correction for each channel
- 2.8 inches True-color 16M TFT-LCD LCD display, touch screen
- Maximum test speed: 100ms / Channel
- compatible SCPI instruction set

■ SPECIFICATION:

SPECIFICATIONS				
	CKT-808		CKT-804	CKT-802 (Discontinued)
Graduation	Thermocouple: J/K/T/E/S/N/B			
Basic Accuracy	0.2%+1℃			
Range	-200 ℃~1300 ℃（variation depend on graduation）			
Resolution	0.1 ℃			
Channel	8 channels		4 channels	2 channels
Speed	Fast: 100ms/channel Medium: 500ms/channel Low: 1s/channel			
Correction	Error correction for each channel			
Comparator	High & low beep function			
Interface	Mini-USB interface			
Option	USB-DISK Interface Micro-SD Card Interface			
Software	Data acquisition software			
Cold Junction Compensation	Accuracy: 0.5℃			
Others	2.8 inches True-color 16M TFT-LCD LCD display, touch screen, USB communication, compatible SCPI instruction set, switch in both English and Chinese; adjustable back light; automatic power off			
GENERAL FEATURES				
Power Supply	Input: 100-240V~50/60Hz 0.35A Output: 9V 1A DC			
Battery Parameters	8.4V, Li, 1400mA rechargeable battery			
Charging Time	Single continuous charging time: Max 200Mins			
Working Time	Brightness 30%≥14 hours, Brightness 50%≥12 hours, Brightness 100%≥9 hours			
Size and Weight	Outside（mm）: 90 (Width)x190(Height)x31 (Depth); Weight: 1KG			
ORDERING INFORMATION				
Accessories	K thermocouple 8/4/2 teams(2m/team); DC power adaptor; Lithium battery; Mini-USB communication cable; Data acquisition software			



CKT

Changzhou
ChuangKai Electronic Co.Ltd